



525 First St.
 Farmington, MN 55024
 Phone: 651-463-BASE (2273)
 Toll Free: 866-391-6216
 Fax: 651-463-2320
 Email: info@base-spec.com
 Website: www.base-spec.com

Base Mat MB-300 and 400 series

SPECIFICATION Aluminum Roll Up Mats - Manufactured to custom sizes and shapes

MAT COMPOSITION	DATA
Manufacturing Process	Corrosion Resistant 6063-T52 Aluminum
Material Composition	Standard Insert: 100% nylon, fusion bonded to backing for durability, or see options below for additional inserts.
PRODUCT DIMENSIONS	
Tread Rails	6063-T52 Aluminum spaced 2" on the center and connected with polyprene thermoplastic rubber hinges or a long lasting size retentive aluminum hinge with 1" x 3/16" slotted holes for maximum drainage.
Frame Recess	"Depth-Grille 3/8"; Depth-Grille & Frame (Level Base) 7/16" Depth-Grille & Frame Options- Surface Mount Ramp Frame *See illustrations for additional frame options.
Blade Dimensions	Size 1 3/4". Spacing between blades is not to exceed 3/16
INSERT OPTIONS	Carpet, Absorb Carpet, Vinyl, Poly-Brush, Vinyl Abrasive
FLAMMABILITY RATING	Passes the required flammability tests required under FF-1-70 (Pill Test).
Standard Load Rating	Note-Ideal for medium to light traffic areas 300 lbs/sq.ft. *Greater load ratings available on request.



Base Mat system shows:

- (1) tapered vinyl frame, (2) mats, (3) vinyl spacer and (4) aluminum frame